

1		2		3		4		5		6		7		8																																																																
REV.NO.		REVISION		DESCRIPTION		DATE		APPROVED																																																																						
A																																																																														
<h3>-SPECIFICATIONS</h3> <table border="1"> <thead> <tr> <th colspan="3">EPR</th> </tr> <tr> <th colspan="3">Rotary Type (Cam Feedback)</th> </tr> <tr> <th>Acting Type</th> <th>Single</th> <th>Double</th> </tr> </thead> <tbody> <tr> <td>Input Signal</td> <td colspan="2">4 ~ 20 mA DC</td> </tr> <tr> <td>Input Resistance</td> <td colspan="2">235 ± 15 Ω</td> </tr> <tr> <td>Air Supply</td> <td colspan="2">Max. 7.0 bar (100 psi) free of oil, water, and moisture</td> </tr> <tr> <td>Operating Angle</td> <td colspan="2">60 ~ 100°</td> </tr> <tr> <td>Pneumatic Connections</td> <td colspan="2">PT(Rc) 1/4 or NPT 1/4</td> </tr> <tr> <td>Electrical Connections</td> <td colspan="2">PF(G) 1/2 or NPT 1/2 or M20 x 1.5</td> </tr> <tr> <td>Protection Class</td> <td colspan="2">Ex dmb IIB+H<sub>2</sub> T6 / Ex dmb IIC T6/T5 / IP66</td> </tr> <tr> <td>Ambient Temperature</td> <td colspan="2">T6: -40°C ~ +55°C T5: -40°C ~ +70°C</td> </tr> <tr> <td>Pressure Gauge</td> <td colspan="2">Stainless steel</td> </tr> <tr> <td>Output Characteristics</td> <td colspan="2">Linear</td> </tr> <tr> <td>Linearity</td> <td>Within ± 1.0 % F.S</td> <td>Within ± 1.5 % F.S</td> </tr> <tr> <td>Sensitivity</td> <td colspan="2">Within ± 0.5 % F.S</td> </tr> <tr> <td>Hysteresis</td> <td colspan="2">Within 1.0 % F.S</td> </tr> <tr> <td>Repeatability</td> <td colspan="2">Within ± 0.5 % F.S</td> </tr> <tr> <td>Air Consumption</td> <td colspan="2">5 LPM (SUP. 1.4 kgf/ )</td> </tr> <tr> <td>Flow Capacity</td> <td colspan="2">80 LPM (SUP. 1.4 kgf/ )</td> </tr> <tr> <td>Material</td> <td colspan="2">Aluminum die-cast</td> </tr> <tr> <td>Weight</td> <td colspan="2">3.3 kg</td> </tr> </tbody> </table>																EPR			Rotary Type (Cam Feedback)			Acting Type	Single	Double	Input Signal	4 ~ 20 mA DC		Input Resistance	235 ± 15 Ω		Air Supply	Max. 7.0 bar (100 psi) free of oil, water, and moisture		Operating Angle	60 ~ 100°		Pneumatic Connections	PT(Rc) 1/4 or NPT 1/4		Electrical Connections	PF(G) 1/2 or NPT 1/2 or M20 x 1.5		Protection Class	Ex dmb IIB+H <sub>2</sub> T6 / Ex dmb IIC T6/T5 / IP66		Ambient Temperature	T6: -40°C ~ +55°C T5: -40°C ~ +70°C		Pressure Gauge	Stainless steel		Output Characteristics	Linear		Linearity	Within ± 1.0 % F.S	Within ± 1.5 % F.S	Sensitivity	Within ± 0.5 % F.S		Hysteresis	Within 1.0 % F.S		Repeatability	Within ± 0.5 % F.S		Air Consumption	5 LPM (SUP. 1.4 kgf/ )		Flow Capacity	80 LPM (SUP. 1.4 kgf/ )		Material	Aluminum die-cast		Weight	3.3 kg	
EPR																																																																														
Rotary Type (Cam Feedback)																																																																														
Acting Type	Single	Double																																																																												
Input Signal	4 ~ 20 mA DC																																																																													
Input Resistance	235 ± 15 Ω																																																																													
Air Supply	Max. 7.0 bar (100 psi) free of oil, water, and moisture																																																																													
Operating Angle	60 ~ 100°																																																																													
Pneumatic Connections	PT(Rc) 1/4 or NPT 1/4																																																																													
Electrical Connections	PF(G) 1/2 or NPT 1/2 or M20 x 1.5																																																																													
Protection Class	Ex dmb IIB+H <sub>2</sub> T6 / Ex dmb IIC T6/T5 / IP66																																																																													
Ambient Temperature	T6: -40°C ~ +55°C T5: -40°C ~ +70°C																																																																													
Pressure Gauge	Stainless steel																																																																													
Output Characteristics	Linear																																																																													
Linearity	Within ± 1.0 % F.S	Within ± 1.5 % F.S																																																																												
Sensitivity	Within ± 0.5 % F.S																																																																													
Hysteresis	Within 1.0 % F.S																																																																													
Repeatability	Within ± 0.5 % F.S																																																																													
Air Consumption	5 LPM (SUP. 1.4 kgf/ )																																																																													
Flow Capacity	80 LPM (SUP. 1.4 kgf/ )																																																																													
Material	Aluminum die-cast																																																																													
Weight	3.3 kg																																																																													
<table border="1"> <thead> <tr> <th>NO.</th> <th>PART NAME</th> <th>MATERIAL</th> <th>Q'ty</th> </tr> </thead> <tbody> <tr> <td>3</td> <td>PRESSURE GAUGE</td> <td>STS304</td> <td>2</td> </tr> <tr> <td>2</td> <td>BASE COVER</td> <td>ALDC12</td> <td>1</td> </tr> <tr> <td>1</td> <td>BASE BODY</td> <td>ALDC12</td> <td>1</td> </tr> </tbody> </table>																NO.	PART NAME	MATERIAL	Q'ty	3	PRESSURE GAUGE	STS304	2	2	BASE COVER	ALDC12	1	1	BASE BODY	ALDC12	1																																															
NO.	PART NAME	MATERIAL	Q'ty																																																																											
3	PRESSURE GAUGE	STS304	2																																																																											
2	BASE COVER	ALDC12	1																																																																											
1	BASE BODY	ALDC12	1																																																																											
<table border="1"> <thead> <tr> <th colspan="2">Protection Class</th> </tr> </thead> <tbody> <tr> <td>F</td> <td>KC flameproof Ex dmb IIB+H<sub>2</sub> T6</td> </tr> <tr> <td>NEPSI</td> <td>flameproof Ex dmb IIB+H<sub>2</sub> T6</td> </tr> <tr> <td>A</td> <td>KC flameproof Ex dmb IIC T6/T5</td> </tr> <tr> <td>D</td> <td>IECEX/ATEX flameproof Ex dmb IIB T6/5</td> </tr> </tbody> </table>																Protection Class		F	KC flameproof Ex dmb IIB+H <sub>2</sub> T6	NEPSI	flameproof Ex dmb IIB+H <sub>2</sub> T6	A	KC flameproof Ex dmb IIC T6/T5	D	IECEX/ATEX flameproof Ex dmb IIB T6/5																																																					
Protection Class																																																																														
F	KC flameproof Ex dmb IIB+H <sub>2</sub> T6																																																																													
NEPSI	flameproof Ex dmb IIB+H <sub>2</sub> T6																																																																													
A	KC flameproof Ex dmb IIC T6/T5																																																																													
D	IECEX/ATEX flameproof Ex dmb IIB T6/5																																																																													
<table border="1"> <thead> <tr> <th>Feedback Shaft</th> <th>Pressure Gauges</th> <th>Pilot Valve Orifice</th> <th>Position Feedback</th> <th>Electrical Connections</th> <th>Dome Indicator</th> <th>Operating Temperature</th> <th>Mounting Bracket</th> </tr> </thead> <tbody> <tr> <td> <ul style="list-style-type: none"> <li>N : NAMUR shaft (direct mounting)</li> <li>A : Fork lever M6x40L</li> <li>B : Fork lever other size on request</li> </ul> </td> <td> <ul style="list-style-type: none"> <li>1 : 6 bar(90psi)</li> <li>2 : 10 bar(150psi)</li> </ul> </td> <td> <ul style="list-style-type: none"> <li>S : Standard</li> <li>M : Small orifice ( 1.0 or 0.7 )</li> </ul> </td> <td> <ul style="list-style-type: none"> <li>N : None (standard)</li> </ul> </td> <td> <ul style="list-style-type: none"> <li>3 : PT(Rc)1/4-PF(G)1/2 (standard)</li> <li>4 : NPT 1/4-NPT1/2</li> <li>5 : PT(Rc)1/4-M20x1.5</li> </ul> </td> <td> <ul style="list-style-type: none"> <li>N : Flat indicator (standard)</li> <li>D : Dome indicator</li> </ul> </td> <td> <ul style="list-style-type: none"> <li>T : 70°C (standard)</li> </ul> </td> <td> <ul style="list-style-type: none"> <li>N : None</li> <li>R : Multi-size NAMUR bracket for DIN VDI/VDE 3845 (130 x 30 x 50 bracket on request)</li> <li>F : DHCT bracket 80x30 for fork lever type</li> <li>E : Multi-size NAMUR bracket for Fork lever type (130 x 30 x 50 bracket on request)</li> </ul> </td> </tr> </tbody> </table>																Feedback Shaft	Pressure Gauges	Pilot Valve Orifice	Position Feedback	Electrical Connections	Dome Indicator	Operating Temperature	Mounting Bracket	<ul style="list-style-type: none"> <li>N : NAMUR shaft (direct mounting)</li> <li>A : Fork lever M6x40L</li> <li>B : Fork lever other size on request</li> </ul>	<ul style="list-style-type: none"> <li>1 : 6 bar(90psi)</li> <li>2 : 10 bar(150psi)</li> </ul>	<ul style="list-style-type: none"> <li>S : Standard</li> <li>M : Small orifice ( 1.0 or 0.7 )</li> </ul>	<ul style="list-style-type: none"> <li>N : None (standard)</li> </ul>	<ul style="list-style-type: none"> <li>3 : PT(Rc)1/4-PF(G)1/2 (standard)</li> <li>4 : NPT 1/4-NPT1/2</li> <li>5 : PT(Rc)1/4-M20x1.5</li> </ul>	<ul style="list-style-type: none"> <li>N : Flat indicator (standard)</li> <li>D : Dome indicator</li> </ul>	<ul style="list-style-type: none"> <li>T : 70°C (standard)</li> </ul>	<ul style="list-style-type: none"> <li>N : None</li> <li>R : Multi-size NAMUR bracket for DIN VDI/VDE 3845 (130 x 30 x 50 bracket on request)</li> <li>F : DHCT bracket 80x30 for fork lever type</li> <li>E : Multi-size NAMUR bracket for Fork lever type (130 x 30 x 50 bracket on request)</li> </ul>																																															
Feedback Shaft	Pressure Gauges	Pilot Valve Orifice	Position Feedback	Electrical Connections	Dome Indicator	Operating Temperature	Mounting Bracket																																																																							
<ul style="list-style-type: none"> <li>N : NAMUR shaft (direct mounting)</li> <li>A : Fork lever M6x40L</li> <li>B : Fork lever other size on request</li> </ul>	<ul style="list-style-type: none"> <li>1 : 6 bar(90psi)</li> <li>2 : 10 bar(150psi)</li> </ul>	<ul style="list-style-type: none"> <li>S : Standard</li> <li>M : Small orifice ( 1.0 or 0.7 )</li> </ul>	<ul style="list-style-type: none"> <li>N : None (standard)</li> </ul>	<ul style="list-style-type: none"> <li>3 : PT(Rc)1/4-PF(G)1/2 (standard)</li> <li>4 : NPT 1/4-NPT1/2</li> <li>5 : PT(Rc)1/4-M20x1.5</li> </ul>	<ul style="list-style-type: none"> <li>N : Flat indicator (standard)</li> <li>D : Dome indicator</li> </ul>	<ul style="list-style-type: none"> <li>T : 70°C (standard)</li> </ul>	<ul style="list-style-type: none"> <li>N : None</li> <li>R : Multi-size NAMUR bracket for DIN VDI/VDE 3845 (130 x 30 x 50 bracket on request)</li> <li>F : DHCT bracket 80x30 for fork lever type</li> <li>E : Multi-size NAMUR bracket for Fork lever type (130 x 30 x 50 bracket on request)</li> </ul>																																																																							
<table border="1"> <thead> <tr> <th colspan="2">PG POWER-GENEX</th> <th colspan="2">TITLE :</th> </tr> </thead> <tbody> <tr> <td colspan="2">http://www.power-genex.com</td> <td colspan="2">ELECTRO PNEUMATIC POSITIONER (EX EPR)</td> </tr> <tr> <td colspan="2">DRAWN : Kim. D. H.</td> <td colspan="2">PRODUCT NAME :</td> </tr> <tr> <td colspan="2">CHECKED : Kim. K. W.</td> <td colspan="2">MODEL :</td> </tr> <tr> <td colspan="2">APPROVED : Kim. K. W.</td> <td colspan="2">EPR</td> </tr> <tr> <td colspan="2">DATE :</td> <td colspan="2">DWC NO.</td> </tr> <tr> <td colspan="2">QUANTITY :</td> <td colspan="2">PG-EP-PP-09</td> </tr> <tr> <td colspan="2">DIMENSION : mm</td> <td colspan="2">REV. NO.</td> </tr> <tr> <td colspan="2">SHEET 1 OF 1</td> <td colspan="2">A</td> </tr> </tbody> </table>																PG POWER-GENEX		TITLE :		http://www.power-genex.com		ELECTRO PNEUMATIC POSITIONER (EX EPR)		DRAWN : Kim. D. H.		PRODUCT NAME :		CHECKED : Kim. K. W.		MODEL :		APPROVED : Kim. K. W.		EPR		DATE :		DWC NO.		QUANTITY :		PG-EP-PP-09		DIMENSION : mm		REV. NO.		SHEET 1 OF 1		A																												
PG POWER-GENEX		TITLE :																																																																												
http://www.power-genex.com		ELECTRO PNEUMATIC POSITIONER (EX EPR)																																																																												
DRAWN : Kim. D. H.		PRODUCT NAME :																																																																												
CHECKED : Kim. K. W.		MODEL :																																																																												
APPROVED : Kim. K. W.		EPR																																																																												
DATE :		DWC NO.																																																																												
QUANTITY :		PG-EP-PP-09																																																																												
DIMENSION : mm		REV. NO.																																																																												
SHEET 1 OF 1		A																																																																												